

List Prices Effective September 6, 2005
Supersedes September 1, 2004

Aluminum 45° Gore Elbow

21

Iron Pipe Size	Price per Gore								
	Insulation Thickness								
	1"	1½"	2"	2½"	3"	3½"	4"	4½"	5"
6"	35.01	35.58	36.21	36.78	37.35	38.05	38.63	39.20	39.85
7"	35.58	36.21	36.78	37.35	37.98	38.63	39.20	39.85	40.34
8"	44.65	45.22	45.02	46.49	47.07	47.64	48.21	48.78	49.35
9"	45.22	45.79	46.49	47.07	47.64	48.21	48.78	49.35	49.91
10"	45.79	46.49	47.07	47.64	48.21	48.78	49.35	49.91	50.49
11"	46.49	47.07	47.64	48.21	48.78	49.35	49.91	50.49	51.07
12"	55.45	56.54	57.65	58.74	60.04	60.94	62.02	63.12	64.22
14"	56.54	57.65	58.74	59.84	60.94	62.02	63.12	64.22	65.31
16"	58.74	59.84	60.94	62.02	63.12	64.22	65.31	66.40	67.49
18"	60.94	62.02	63.12	64.22	65.31	66.40	67.49	68.58	69.68
20"	63.12	64.22	65.31	66.40	67.49	68.58	69.68	70.78	84.54
22"	65.31	66.27	67.49	68.58	69.68	70.78	84.54	85.64	86.73
24"	75.93	77.02	78.13	79.22	95.79	96.88	97.98	99.08	118.54
26"	101.78	111.83	134.56	136.17	137.81	139.42	141.04	142.66	144.29
28"	134.56	136.17	137.81	139.42	141.04	142.66	144.29	145.90	152.15
30"	137.81	139.42	141.04	153.92	155.53	157.16	158.11	160.40	162.02

Fittings are manufactured to "ASTM" recommended dimensional standard C450 and "Manufacturers simplified dimensional standards".