

List Prices Effective August 1, 2006

Supersedes January 16, 2006

Deep Corrugated Sheets-Thermoclad® PLUS

12

Aluminum Thermoclad® 1¼" and 2½" Corrugations	Shipping Weight lbs./sq. ft.	Price per sq. ft. Formed	
		Smooth	Stucco Embossed
.016" x 33"	0.230	3.24	3.32
.020" x 33"	0.281	3.72	3.80
.024" x 33"	0.361	4.36	4.48
.032" x 33"	0.452	5.72	5.84
.040" x 33"	0.591	6.82	6.94

All prices include Thermoclad® PLUS moisture retarder

Standard Nominal dimensions: 2-1/2" x 1/2" or 1-1/4" x 1/4" x 33" Formed Width

Orders less than 100 sheets, add \$75.00 to **net price** for set-up and skid charge

1-1/4" x 1/4" and 2-1/2" x 1/2" corrugated available in lengths up to 14' - 0"

Protective Coatings

The substrate receives a four stage cleaning process and is non-chromate conversion coated before the thermosetting enamel coatings are applied.

The interior laminate grade coating is opaque white and is applied at 0.6 mil thickness to provide excellent corrosion protection on the surface in contact with insulation. In addition to the thermosetting enamel the interior surface is further protected by a 3 mil three layer co-extruded factory heat laminated Polysurlyn film. This combination of protective coatings on the interior provides the best protection possible.

A specially designed un-tinted 0.4 mil thick coating is applied to the exterior surface, and provides corrosion protection from the atmospheric elements. Both coatings are baked on at 420 degrees F in a continuous coil coating process.

All Sales Taxes Extra Where Applicable

F.O.B. OUR WAREHOUSE

Presence of Pricing Does Not Necessarily
Indicate Immediate Availability of Material

Terms: Net 30 days